

# Rollin' Stone

54" / Type II / 20 oz. LOW VOC RECYCLED CONTENT



AZ53540RT Shine A Light

## PHYSICAL PROPERTIES

**Weight:** 20 oz. PLY/620 G/PLM 13.3 oz. PSY/451 G/PSM

**Backing:** Osnaburg **Width:** 54 in./137 cm

**Match:** Reverse, random match

Custom colors, weights, and micro venting available

Meets or exceeds Federal Specification CCC-W-408D for Type II Wallcovering

## FIRE SAFETY

- Class "A" fire rated - tested in accordance with ASTM-84 Tunnel Test
- Passes Class "A" NFPA 101 Life Safety Code
- Passes NFPA 286 Corner Burn Test
- Tested in accordance with CAN/ULC S102.2

## ENVIRONMENT & HEALTH

- 10% recycled content (varied blend of pre-consumer and remanufactured material)
- Certified to NSF/ANSI 342 Sustainability Assessment: ask distributor for details
- Meets California Section 01350 IAQ test requirements for wallcovering
- Complies with USGBC LEED v4 Criteria, under Indoor Environmental Quality (CDPH/EHLB/Standard Method Version 1.1, 2010)

## WARRANTY

5 year warranty against manufacturing defects.

Additional information is available at: [symphonywallcovering.com](http://symphonywallcovering.com)